


Display Data Address

Character	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
Line 1	80	81	82	83	84	85	86	87	88	89	8A	8B	8C	8D	8E	8F	90	91	92	93
Line 2	CO	C1	C2	C3	C4	C5	C6	C7	C8	C9	CA	CB	CC	CD	CE	CF	D0	D1	D2	D3
Line 3	94	95	96	97	98	99	9A	9B	9C	9D	9E	9F	AD	A1	A2	A3	A4	A5	A6	A7
Line 4	04	D5	D6	D7	D8	D9	DA	DB	DC	DD	DE	DF	E0	E1	E2	E3	E4	E5	E6	E7

NOTES:

1. DISPLAY TYPE: STN, BLUE MODE, TRANSMISSIVE /NEGATIVE.
2. DRIVER METHOD: 1/32 DUTY,1/5 BIAS,VDD=5.0V,VOP=4.2V
3. VIEWING DIRECTION: 6 O'CLOCK.
4. IC DRIVER:KS0066 OR EQUIVALENT
5. OPERATING TEMP: -20°C ~ +70°C.
6. STORAGE TEMP: -30°C ~ +80°C.
7. LED BACKLIGHT: BOTTOM Y/G LEDA-LEDK=5V
8. ALL UNMARKED TOLERANCES: ±0.5mm
9. RoHS COMPLIANT



DISPLAY PATTERN