



Terminal No.	Pin Name
1	Vss
2	Vcc
3	Vo
4	RS
5	R/W
6	E
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7
15	A
16	K

- NOTE:**
- 1.DISPLAY TYPE: STN/YELLOW-GREEN MODE
  - 2.VIEWING DIRECTION: 6:00
  - 3.POLARIZER MODE: TRANSMISSIVE/POSITIVE
  - 4.DRIVE METHOD: 1/16 DUTY 1/5 BIAS
  - 5.LCD OPERATING VOLTAGE: 4.7V
  - 6.OPERATING TEMP: -20°C~+60°C
  - 7.STORAGE TEMP: -30°C~+80°C
  - 8.BACKLIGHT: LED\Yellow-Green If=390ma,V(type)=4.2
  - 9.UNMARKED TOLERANCE: MECHANIC TOL ±0.3mm
  - 10.DRIVER/CONTROLLER IC: ST7066U-0A
  - 11.BEZEL IS TO BE PAINTED BLACK
  - 12.DIMENSION TO BE CONTROLLED MARK
  - 13.REQUIREMENTS ON ENVIRONMENTAL PROTECTION: RoHS

NOVO LCD Co.

DRAWN BY:	TITLE: NL4002AYYC	
CHECKED BY:	PURPOSE: G-1	
APPROVED BY:	UNIT: mm	
CONFIRMED BY:	SCALE: 1:1	
		SHEET NO: 1 OF 1