



- 13.30±0.5
- 11.00±0.3
- 8.15±0.3
- 1.50±0.3
- 2.00±0.3
- 2.50±0.2
- 3.40±0.1



- NOTES:**
1. DISPLAY TYPE: a-Si TFT
  2. DISPLAY MODULE: Transflective, Normally White
  3. VIEWING DIRECTION: 12:00 O'clock
  4. OPERATING TEMP: -20° C---+70° C
  5. STORAGE TEMP: -30° C---+80° C
  6. Backlight: LED
  7. RoHS Compliant

PIN DESCRIPTION	
1	IM0 DB2
2	IM1 DB1
3	IM2 DB0
4	IM3 SDD
5	RESSET SDI
6	VS YNC RD
7	HS YNC RD
8	DOTCLK RS
9	ENABLE CS
10	DB17 FMARK
11	DB16 TDVCC
12	DB15 VCC
13	DB14 VCI
14	DB13 GND
15	DB12 X+(NC)
16	DB11 X-(NC)
17	DB10 Y-(NC)
18	DB9 Y+(NC)
19	DB8 LEDA
20	DB7 LEDK1
21	DB6 LEDK2
22	DB5 LEDK3
23	DB4 LEDK4
24	DB3

**NOVO LCD Co.**

DRAWN BY:	TITLE: NL0283BUG	SCALE:	1:1
CHECKED BY:	DWG NO:	UNIT:	mm
APPROVED BY:	DWG NAME:	SHEET NO:	OF
CONFIRMED BY:			